

10-26-00

A

10/25/00
JC951 U.S. PTO

IBM Docket No. FR9-1999-0110 US1

JC926 U.S. PTO
09/696518
10/25/00

In the United States Patent and Trademark Office Patent Application Transmittal

Transmitted herewith for filing is the Patent Application of:

Inventor(s): Olivier Daude, Olivier Hericourt

For: Method and System for Preventing Unauthorized Server Interference in an Internet Protocol Network

Enclosed are

- 48 pages of specification, including 39 claims, plus 4 sheets of drawings.
- X An assignment of the invention to International Business Machines Corporation, Armonk, New York 10504.
- X A certified copy of a/an **European** application.
- X Declaration and Power of Attorney.
PTO-1449 & references
- X A return post card
- Other:

Filing Fee Calculation (For Other Than Small Entity)

| | | | | | | |
|------------------------------------|-------|-------|-------|--|----------------|-------------------|
| Basic Fee: | | | | | | \$710.00 |
| Claims Fees: | Filed | Limit | Extra | | Rate per Extra | |
| Total claims: | 39 | 20 | 19 | | \$18.00 | \$342.00 |
| Independent claims: | 3 | 3 | 0 | | \$80.00 | \$0.00 |
| Multiple Dependent Claim Presented | | | | | \$270.00 | \$0.00 |
| Total: | | | | | | \$1,052.00 |

Please charge Deposit Account **09-0464** for the **Total** set forth above. The Commissioner is authorized to charge payment of any additional filing fees required under 37 CFR §1.16 and any patent application processing fees under 37 CFR §1.17 or to credit any overpayment to the identified account. A duplicate copy of this sheet is enclosed.

| | |
|---|---------------|
| Express Mail Certificate | |
| Express Mail Label No: | E1855834947US |
| Date: | Oct. 25, 2000 |
| I hereby certify that I am depositing the papers identified above with the U.S. Postal Service "Express Mail-Post Office to Address" service on the above date, addressed to the Assistant Commissioner for Patents, Washington, DC 20231 | |
|  Sandra S. Christopher | |

BY: 

Daniel E. McConnell

Attorney of Record Reg. No. 20,360

Date: Oct. 25, 2000

IBM Corporation 2Y7/B656
Intellectual Property Law
PO Box 12195
Res. Tri. Park, NC 27709

Telephone: 919-543- 1105 FAX 919-543-3634

09696518 10/25/00

METHOD AND SYSTEM FOR PREVENTING UNAUTHORIZED SERVER
INTERFERENCE IN AN INTERNET PROTOCOL NETWORK

BACKGROUND OF THE INVENTION

5

1. Technical Field:

10

The present invention relates to computer networks, and in particular to a method and system in an Internet Protocol (IP) network for detecting and neutralizing one or a plurality of unauthorized Dynamic Host Configuration Protocol (DHCP) servers.

15

2. Description of the Related Art:

Internet

20

The Internet is a global network of computers and computers networks (the "Net"). The Internet connects computers that use a variety of different operating systems or languages, including UNIX, DOS, Windows, Macintosh, and others. To facilitate and allow the communication among these various systems and languages, the Internet uses a language referred to as TCP/IP ("Transmission Control Protocol/Internet Protocol"). TCP/IP protocol supports three basic applications on the Internet:

25

- (1) transmitting and receiving electronic mail,
- (2) logging into remote computers (the "Telnet"),

30

and

- (3) transferring files and programs from one computer to another ("FTP" or "File Transfer Protocol").

IP Addresses

Routers are utilized to interconnect two networks by forwarding packets from one network to the other. The term "IP router" is also used because the routing function is part of the IP network layer of the TCP/IP protocol.

IP addresses are utilized by the IP protocol to uniquely identify a host on the Internet. Strictly speaking, an IP address identifies an interface that is capable of sending and receiving IP datagrams, and one system can have more than one of such interfaces. However, both hosts and routers must have at least one IP address, so this simplified definition is acceptable. IP datagrams (data packets exchanged between hosts) are transmitted by a physical network attached to the host, wherein each IP datagram contains a source IP address and a destination IP address.

IP addresses are represented by a 32-bit unsigned binary value which is usually expressed in a dotted decimal format. For example, 9.167.5.8 is a valid Internet address. This numeric form is utilized by the IP software. The mapping between the IP address and an easier-to-read symbolic name, for example myhost.ibm.com, is performed by a Domain Name System (DNS).

IP Subnets

Due to the explosive growth of the Internet, assigning IP addresses is not flexible enough to allow efficiently facilitate changes in local network configurations. Such changes might occur when a new type

of physical network is installed at a location. A growing number of hosts within a local network may also precipitate such configuration changes by requiring that the local network split into two or more separate networks. In addition, growing intranetwork distances require to divide a network into smaller networks separated by gateways.

The concept of subnets has been introduced to avoid the need to request additional IP network addresses in these cases. Subnets can be assigned locally, since the original single network still appears as one IP network with respect to the larger IP internetwork context. To designate a subnet, the host number within an IP address header is subdivided into a network number and a host number. This second network is termed "subnetwork" or "subnet". The original network now includes multiple subnets, and an IP address associated therewith is interpreted as:

<network number><subnet number><host number>.

The combination of the subnet number and the host number is often termed "local address" or "local part". Subnetting is implemented in such a way that it is transparent with respect to remote networks. A host within a network that includes subnets is aware of the subnetting while hosts in outside networks are not (the local host still regards the local part of the IP address as a host number).

The manner in which the local part of the IP address is divided into subnet number and host number is freely chosen by the local network administrator (i.e., any bits in the local part of the address can be utilized to designate a subnet). The division of the original local part of the IP address into a subnet and host name is performed utilizing a subnet mask which is a 32-bit number. Zero bits in a subnet mask indicate bit positions ascribed to the host number, and ones indicate bit positions ascribed to the subnet number. The bit positions in the subnet mask belonging to the network number are set to ones but are not utilized. Subnet masks, like IP addresses are usually written in dotted decimal form.

World Wide Web

With the increasing size and complexity of the Internet, tools that are often called navigators or navigation systems have been developed to help find information on the network. Navigation systems include standards such as Archie, Gopher and, most well-known, the World Wide Web ("WWW" or "the Web"). In addition to serving as an Internet-based navigation system, the Web is also an information distribution and management system for the Internet. The Web provides an end user with a seamlessly integrated format of information, including still images, text, audio and video. A user on the Web using a graphical user interface may transparently communicate with different host computers on the system, different system applications, and different information formats for files and documents including text, sound, and graphics.

Uniform Resource Locators

A resource of the Internet is unambiguously identified by a Uniform Resource Locator (URL), which is a pointer to a particular resource at a particular location. A URL specifies the protocol utilized to access a server (e.g. HTTP, FTP,...), the name of the server, and the location of a file on that server.

Hyper Text Transfer Protocol

Each Web page that appears on client monitors may appear as a complex document that integrates, for example, text, images, sounds and animation. Each such page may also contain hyperlinks to other Web documents so that a user at a client computer using a mouse may click on icons and may activate hyperlink jumps to a new page (which is a graphical representation of another document file) on the same or a different Web server.

A Web server is a software program on a Web host computer that answers requests from Web clients, typically over the Internet. All Web servers utilize a Hyper Text Transfer Protocol (HTTP) to communicate with Web clients. All types of data can be exchanged among Web servers and clients using HTTP, including Hyper Text Markup Language (HTML), graphics, sound and video. HTML describes the layout, contents and hyperlinks of the documents and pages. When browsing, a Web client converts user specified commands into HTTP GET requests, connects to the appropriate Web server to retrieve information, and waits for a response. The response from the server can be the requested document or an error message. After the document or an error message is

returned, the connection between the Web client and the Web server is closed.

HTTP version 1.0 is a stateless protocol in which there is no continuous connection between each client and each server. A Web client using HTTP receives a response as HTML data or other data. The new HTTP version 1.1 breaks this barrier of stateless protocol by keeping the connection between the server and client alive under certain conditions.

Domain Names

The host or computer names (like www.entreprise.com) are translated into numeric Internet addresses (like 194.56.78.3), and vice versa, by using a method called DNS ("Domain Name Service"). DNS is supported by network-resident servers, also known as domain name servers or DNS servers.

Dynamic IP

For dynamic IP there are generally three pieces of information needed by a system to communicate on a TCP/IP network. First, there is an IP address utilized to uniquely identify a particular system on the network. Next, a subnet mask is utilized to distinguish the network and subnet parts of the address. Finally, an address of at least one router is required if the system communicates with devices outside its immediate subnet.

While at a minimum these three values must be programmed into each device that participates in TCP/IP communications, the number of necessary parameters will

5

10

15

20

25

30

delivers configuration information to a client that has not been manually configured.

5 The latter BOOTP process involves the following steps. First, a BOOTP client determines its own hardware address, normally from a ROM (Read Only Memory) on the hardware. Next the client sends its hardware address in a UDP (User Datagram Protocol) datagram to the server. The client should utilized its IP address and/or the
10 address of the server if it has these values. However, BOOTP clients generally have no IP configuration data at all. If the client does not know its own IP address, it utilizes 0.0.0.0. If the client does not know the server's IP address, it utilizes the limited broadcast address (255.255.255.255) on the server's UDP port number
15 67.

After the server receives the datagram, it performs a lookup to identify the hardware address of the client in its configuration file. The hardware address contains the client's IP address. The server then supplies the required address information in the appropriate UDP
20 datagram fields, and returns the dataframe to the client using client's UDP port 68. Upon receiving the reply, the BOOTP client will record its own IP address and begin the bootstrap process.
25

BOOTP is a recommended draft standard protocol. BOOTP specifications can be found in *RFC 951 - Bootstrap Protocol*. There are also updates to BOOTP, some relating
30 to inter operability with DHCP (Dynamic Host Configuration Protocol) that are described in *RFC 1542 -*

Clarifications and Extensions for the Bootstrap Protocol, which updates RFC 951 and RFC 2132 – DHCP Options and BOOTP Vendor Extensions.

Dynamic Host Configuration Protocol (DHCP)

Dynamic Host Configuration Protocol (DHCP) provides a framework for passing configuration information to hosts on a TCP/IP network. DHCP is based on the BOOTP protocol, and adds the capability of automatically allocating reusable network addresses and additional configuration options. DHCP messages utilize UDP port 67, the BOOTP server's well-known port, and UDP port 68, the BOOTP client's well-known port.

DHCP consists of two components including a protocol that delivers host-specific configuration parameters from a DHCP Server to a host, and a mechanism for the allocation of temporary or permanent network addresses to hosts.

IP requires the setting of many parameters within the protocol implementation software. Because IP can be utilized on many dissimilar types of network hardware, values for those parameters cannot be presumed. A distributed address allocation scheme based on a polling / defence mechanism, for discovering network addresses currently in use, cannot guarantee unique network addresses because hosts may not always be able to protect their network addresses.

DHCP supports three mechanisms for IP address allocation. First DHCP supports automatic allocation in

which DHCP assigns a permanent IP address to the host.
Second, DHCP supports dynamic allocation in which DHCP
assigns an IP address for a limited period of time.
Finally, DHCP supports manual allocation in which the
host's address is assigned by a network administrator.

DHCP is a draft standard protocol having an elective
status. The current DHCP specifications can be found in
RFC 2131 - Dynamic Host Configuration Protocol and *RFC*
2132 - DHCP Options and BOOTP Vendor Extensions.

Configuration Parameters Repository

DHCP provides persistent storage of network
parameters for network clients. A DHCP server stores a
key-value entry for each client. The key is a unique
identifier such as, for example, an IP subnet number and
a unique identifier within the subnet (normally a
hardware address). The key-value contains the
configuration parameters last allocated to this
particular client.

One effect of this persistent key-value storage is
that the server will always tend to allocate the same IP
address to a DHCP client, provided the pool of addresses
is not over-subscribed and the previous address has not
already been allocated to another client.

DHCP Considerations

DHCP allocation of IP addresses and configuration
parameters relieves the network administrator of a great
deal of manual configuration work. The ability to move a
device from network-to-network and to automatically

obtain valid configuration parameters for the current network can be of great benefit to mobile users. Also, because IP addresses are only allocated when clients are actually active, it is possible, by the use of reasonably short lease times and the fact that mobile clients do not need to be allocated more than one address, to reduce the total number of addresses in use in an organization.

However, the following should be considered when implementing DHCP. First, DHCP is built on UDP, which is, as yet, inherently insecure. In normal operation, an unauthorized client could connect to a network and obtain a valid IP address and configuration. To prevent this, IP addresses can be preallocated to particular MAC (Medium Access Control) addresses. This solution, however introduces additional administrative workload and negates the benefit of recycling addresses. Another problem with DHCP is the possibility that unauthorized DHCP servers may be implemented which send false and potentially disruptive information to clients.

Regardless of whether static or dynamic address allocation is utilized, it is generally not possible in a DHCP environment to predetermine the IP address of a client at any particular point in time. As such, the DNS servers will not likely contain valid host-name-to-IP-address mappings for the clients. The only alternative is to manually assign IP addresses to clients and then administer the client mappings in the DNS accordingly.

BOOTP and DHCP Interoperability

The format of DHCP messages is based on the format of BOOTP messages, thus enabling BOOTP and DHCP clients to interoperate in certain circumstances. Support for BOOTP clients at a DHCP server must be configured by a system administrator.

Dynamic Domain Name System

In order to take advantage of DHCP, while retaining the capability to locate any specific host by means of a meaningful label such as its host name, the following extensions to the DNS are required. First, a method is required for the host name to be addressed to a mapped entry for a client in the domain name server to be updated, once the client has obtained an address from a DHCP server. A method is required for the reverse address to host name mapping once the client obtains its address.

In addition, updates to the DNS must take effect immediately, without the need for intervention by an administrator. Updates to the DNS must be authenticated to prevent unauthorized hosts from accessing the network and to stop imposters from using an existing host name and remapping the address entry for the unsuspecting host to that of its own. Finally, a method is required which allows primary and secondary DNS servers to quickly forward and receive changes as entries are being updated dynamically by clients. In short, a secure Dynamic Domain Name System (DDNS) is necessary.

In summary, in the DHCP and DDNS environment, DHCP supplies a valid IP address to a device at the point in time at which the device is attached to the network. DDNS provides a method for locating that device within the network in accordance with its host name, and for determining the IP address allocated to the device.

More explanations about the domain presented in the above sections can be found in the following publications incorporated herewith by reference: TCP/IP Tutorial and Technical Overview by Martin W. Murhammer, Orcun Atakan, Stefan Bretz, Larry R. Pugh, Kazunari Suzuki, David H. Wood published by IBM International Technical Support Organization; "Internet in a nutshell" by Valerie Quercia, published by O'Reilly, October 1997; Request For Comments (RFCs) from the Internet Engineering Task Force (IETF); and RFC 2131: Dynamic Host Configuration Protocol.

When a DHCP client needs to acquire configuration information such as an IP address (for instance when the DHCP client is powered on), the DHCP client usually broadcasts a request to retrieve the configuration information from a DHCP server. The DHCP service is provided by one or more DHCP servers, in order to optimally adjust configuration parameters. Due to the nature of the DHCP protocol which is based on UDP (User Datagram Protocol) BOOTP broadcast, any DHCP server attached to the IP network can answer requests from DHCP clients and can therefore provide DHCP clients with configuration parameters. The DHCP client selects and utilizes the configuration parameters included within one

of the answers received from the DHCP servers (usually, the DHCP client selects and utilizes the configuration parameters received from the first DHCP server to respond).

5

Once a DHCP client has retrieved the requested configuration information (including its IP address) from a DHCP server, the DHCP client can then utilize the configuration information to access resources within the IP network. For example, a DHCP client utilizes its IP address to access a WEB server within the IP network.

10

Some access and security considerations are associated with the configuration information retrieved by DHCP clients. For example, the IP address retrieved and utilized by a DHCP client may be utilized by a WEB server to identify the DHCP client. The WEB server can then only respond to requests from the DHCP client having this specific IP address. The DHCP client configured with the specific IP address is therefore able to retrieve information from the WEB server (for example confidential information). A DHCP client configured with an IP address different from the specific IP address is not able to retrieve confidential information from the WEB server.

25

The nature of the configuration information provided by the DHCP servers may be determined by a network administrator. Erroneous configuration information may result in DHCP clients having problems accessing resources within the IP network. For example, a WEB server may only accept requests sent by DHCP clients that

30

00555513-10300

have valid IP addresses (an IP address included within a list of IP addresses controlled by the network administrator). If the IP address retrieved from a DHCP server by a DHCP client is incorrect (an IP address which is not included within the list of valid IP addresses), the WEB server will reject requests originated from the DHCP client.

Inversely, an incorrect IP address provided to a DHCP client may enable the DHCP client to access a WEB server that the client should not have access to. A security problem is thus presented because the DHCP client may access confidential information it is not supposed to access.

DHCP servers that provide DHCP clients with erroneous configuration information are called "unauthorized DHCP servers", or "invalid DHCP servers", because they are not properly under the control of a network administrator. Unauthorized DHCP servers may be unintentionally attached to an IP network for example by someone testing DHCP functions, or may be deliberately attached to create access problems within the IP network.

From the foregoing, it can be appreciated that there exists a need to detect any unauthorized DHCP server attached to the IP Network. Furthermore it would be useful to inhibit any unauthorized DHCP server attached to the IP network from providing unauthorized access to IP network resources.

SUMMARY OF THE INVENTION

A method and system for preventing unauthorized dynamic host configuration servers from responding to client configuration requests in an Internet Protocol (IP) network are disclosed herein. In accordance with the method of the present invention multiple network clients are simulated within a server checker client. At least one unauthorized dynamic host configuration server is then detected utilizing the server checker client within said IP network. Upon detection of an unauthorized dynamic host configuration server, configuration requests are delivered from the server checker client to the detected unauthorized dynamic configuration server such that the unauthorized dynamic host configuration server is unable to respond to configuration requests from actual network clients.

All objects, features, and advantages of the present invention will become apparent in the following detailed written description.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel and inventive features believed characteristics of the invention are set forth in the appended claims. The invention itself, however, as well as a preferred mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative detailed embodiment when read in conjunction with the accompanying drawings, wherein:

Figure 1 illustrates a conventional IP host configuration system;

Figure 2 depicts a DHCP checker client in accordance with a preferred embodiment of the present invention;

Figure 3 is a flow diagram view illustrating the logic flow of an invalid server detector in accordance with a preferred embodiment of the present invention; and

Figure 4 is a flow diagram view depicting the logic flow of an invalid server denial handler in accordance with a preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

IP ADDRESS ALLOCATION

With reference now to the figures, and in particular with reference to **Figure 1** there is illustrated a conventional IP host configuration system in which DHCP client/server interactions are described in the context in which the DHCP client is not aware of its network address. More particularly, **Figure 1** shows the acquisition mechanism by which a DHCP client acquires an IP address and the IP minimal configuration parameters provided by a DHCP server within an IP network.

A DHCP client **101** broadcasts a request on its local physical subnet **103**. The request is forwarded by any router having a BOOTP forwarding mechanism. When the request is received by a DHCP server **102**, the DHCP server checks whether or not it is able to answer the DHCP client. If the DHCP server has an available IP address within its address database, a positive answer is returned to DHCP client **101**. DHCP client **101** selects the first DHCP server for which a positive answer is received and confirms to this server its agreement.

Specifically, the allocation of a new network address as described above includes the following steps. First, DHCP client **101** broadcasts a request (a DHCPDISCOVER message) on its local physical subnet **103**. The request may include desired options such as network address suggestion or lease duration.

Each DHCP server may respond with a message (a DHCP OFFER message) that includes an available network address and other configuration options. The DHCP server may record the address as offered to DHCP client 101 to prevent the same address being offered to other DHCP clients in the event of further messages being received before the first DHCP client has completed its configuration.

DHCP client 101 receives one or more messages from one or more of DHCP servers 102. DHCP client 101 chooses one response based on the configuration parameters offered and broadcasts a message (a DHCP REQUEST message) that includes the DHCP server identifier option to indicate which message it has selected and the requested IP address option, taken from the DHCP client IP address in the selected offer.

DHCP servers 102 receive the messages broadcasted by DHCP client 101. Those DHCP servers not selected utilize the message as notification that the DHCP client has declined that DHCP server's offer. The selected DHCP server commits the binding for the DHCP client to persistent storage and responds with a message containing the configuration parameters for the requesting DHCP client. The DHCP client receives the message with configuration parameters and performs a final check on the parameters. At this point the DHCP client is configured.

DHCP Checker Client

The present invention relates to a system and method for detecting and neutralizing unauthorized DHCP servers attached to an IP network. **Figure 2** depicts a system that is utilized for detecting and neutralizing unauthorized DHCP servers according to the present invention.

DHCP clients **201** on an IP network **202** retrieve their configuration information from DHCP servers **203** and **204** attached to the IP network. DHCP servers **203** are authorized DHCP servers that are controlled by a network administrator. Authorized DHCP servers **203** provide valid configuration information to the DHCP clients **201**.

One or more DHCP servers **204**, that are also attached to IP network **202**, are unauthorized DHCP servers (also referred to as an invalid DHCP server). They are not controlled by a network administrator and they provide invalid configuration information to the DHCP clients **201**. Such unauthorized DHCP servers may be unintentionally attached to IP network **202** by someone testing DHCP functions, or may be intentionally attached to sabotage IP network **202**.

As further illustrated in **Figure 2**, a DHCP checker client **205** is also attached to IP network **202** in accordance with the preferred embodiment of the present invention. DHCP checker client **205** is preferably a computer program that can run on any system (a workstation, for example) attached to IP network **202**.

DHCP checker client 205 carries out the method for detecting and neutralizing one (or multiple) unauthorized DHCP server 204.

5 DHCP checker client 205 includes a DHCP server table 206. DHCP server table 206 (a flat file in a preferred embodiment) may be created by the network administrator responsible for the IP network. DHCP server table 206 includes a list of authorized DHCP servers. Each
10 authorized DHCP server 203 is preferably identified within DHCP server table 206 in accordance with its respective IP address.

When DHCP checker client 205 is started, an invalid server detector component 207 periodically sends requests 209 to retrieve configuration information 210 from DHCP servers 203 and 204. Invalid server detector 207 detects one or more unauthorized DHCP servers 204 by comparing a "server identifier" option included in the DHCP OFFER message returned by the DHCP servers in configuration information 210 with authorized server identification data in DHCP server table 206.

25 In response to one or more unauthorized DHCP servers 204 being detected by invalid server detector 207, DHCP checker client 205 automatically activates an invalid server denial handler component 208. Invalid server denial handler 208 simulates multiple DHCP clients by sending a large number of requests 211 to each
30 unauthorized DHCP server 204 detected by invalid server detector 207, for retrieving 212 configuration

information. The requests **211** include DHCPDISCOVER and DHCPREQUEST unicast messages, and utilizes 'giaddr', 'chaddr', and 'ciaddr' fields of the messages. The number of the requests depends on the configuration of the DHCP checker client.

By simulating multiple DHCP clients, invalid server denial handler **208** prevents unauthorized DHCP servers **204** from answering actual DHCP clients **201** that request configuration information. As a result, the number of DHCP clients **201** receiving erroneous configuration information by the unauthorized DHCP servers **204** is minimized. Additionally, access problems caused by the unauthorized DHCP servers are also minimized.

Unauthorized DHCP servers are, in effect, neutralized in response to invalid server denial handler **208** sending a large number of requests **211** to each unauthorized DHCP server **204**. This neutralization results from each unauthorized DHCP server **204** being overloaded with the requests and the corresponding configuration responses **212**. In response to configuration requests and the resulting responses **212**, many if not all of the IP addresses allocatable by unauthorized DHCP server **204** are reserved for DHCP checker client **205** and are therefore no longer available for other DHCP clients **201**.

After such neutralization, each is too busy to answer **214** requests **213** that are sent by DHCP clients **201**. Unauthorized DHCP server **204** is depleted of the

available IP addresses which can be provided to DHCP clients 201. The number of DHCP clients 201 that may potentially retrieve 214 configuration information from unauthorized DHCP servers 204 is therefore minimized.

INVALID SERVER DETECTOR

Invalid server detector 207 is preferably a computer program that periodically requests and retrieves configuration information from DHCP servers 203 and 204. Invalid server detector 207 identifies unauthorized DHCP servers 204 by comparing server identification data in DHCP server table 206 with the "server identifier" option included in the DHCPOFFER message returned 210 by the DHCP servers.

Invalid server detector 207 is activated when the DHCP checker client starts. With reference now to **Figure 3**, there is depicted a flow diagram illustrating the logic flow of invalid server detector 207 for detecting invalid DHCP servers in accordance with a preferred embodiment of the present invention.

As depicted at step 301, the invalid server detection process begins with invalid server detector 207 requesting an IP address. During step 301, DHCP checker client 205 appears as a typical DHCP client within respect to DHCP servers 203 and 204. Invalid server detector 207 sends a DHCPDISCOVER message on the IP network, in order to request configuration parameters (including an IP address) from a DHCP server. The DHCPDISCOVER message is a broadcast message which is sent

to any system attached to the IP network.

Next, as shown at step 302, invalid server detector 207 waits for DHCPOFFER messages. Each of DHCP servers 203 and 204 that satisfy the DHCPDISCOVER request sent by invalid server detector 207, responds to the request with a DHCPOFFER message. The DHCPOFFER message includes the configuration information (including the IP address) proposed by the responding DHCP server. In addition the DHCPOFFER message includes the 'server identifier' option. The 'server identifier' option includes the address (the IP address) of the respondent DHCP server. The time over which invalid server detector 207 waits before receiving the DHCPOFFER message sent by each DHCP server is preferably a configuration parameter of DHCP checker client 205.

Proceeding to step 303, invalid server detector 207 releases the IP address proposed by each DHCP server. Authorized DHCP servers 203 may have sent a DHCPOFFER to propose configuration parameters. Invalid server detector 207 therefore releases the proposed configuration parameters so that they can be utilized by actual DHCP clients 201. In order to release the IP address proposed by each DHCP server, invalid server detector 207 sends a DHCPREQUEST broadcast message that includes a 'server identifier' option. The 'server identifier' option is not set by invalid server detector 207 with the identifier of the DHCP server that has been selected, but instead includes the identifier (the IP address) of a DHCP server that does not exist (10.1.1.1,

for example).

When each DHCP server **203** and **204** receives the DHCPREQUEST message, it compares the IP address included within the 'server identifier' option and its own IP address. Since the 'server identifier' and its IP address are different, the DHCP server marks the proposed configuration parameters as being available again for other DHCP clients.

As illustrated at step **304**, invalid server detector **207** builds a list (called "List_R") of the DHCP servers which have sent a DHCPOFFER. The list "List_R" includes the IP address of each DHCP server to which the DHCPOFFER message has been sent. In a preferred embodiment, "List_R" is constructed using the 'server identifier' option included in each DHCPOFFER message received in **202**. The IP address of each DHCP server which has sent a DHCPOFFER is extracted from the 'server identifier' option.

Proceeding to step **305**, invalid server detector **207** retrieves a list (called "List_A") of all authorized DHCP servers. This list is retrieved from a DHCP server table **306** that is analogous to DHCP server table **206** in **Figure 2**. "List_A" includes the IP address of each authorized DHCP server.

Invalid server detector **207** extracts from "List_R" a list (called "List_D") of the DHCP servers which are not in "List_A" as shown at step **307**. "List_D" therefore includes the IP address of each unauthorized (also

referred to as invalid) DHCP server.

As depicted at step 308, invalid server detector 207 determines whether or not "List_D" is empty. If "List_D" is determined to be empty, no unauthorized (invalid) DHCP server has been detected, and as illustrated at step 309, invalid server detector 207 may store a message indicating that no invalid DHCP server has been detected. This message may be, for example, stored in a file located within the DHCP checker client. The operational cycle for invalid server detector 207 then concludes as shown at step 310. The DHCP checker client then initiates another cycle in which invalid server detector 207 begins the procedure for detecting unauthorized DHCP servers starting at step 301. The inter-cycle period in which DHCP checker client 205 waits before starting invalid server detector 207 is preferably a configuration parameter of DHCP checker client 205.

If, however, as depicted at step 311, it is determined at step 308 that "List_D" is not empty, one or more unauthorized (invalid) DHCP servers have been detected. In such a case, and as illustrated at step 311, invalid server detector 207 may store a message indicating that one or multiple invalid DHCP servers have been detected. This message may include the IP address of each the detected unauthorized DHCP servers, and is stored in a file located within DHCP checker client 205. A network alert including the unauthorized server message can also be sent to a network administrator. The network administrator can then (for example) disconnect

each unauthorized DHCP server from the IP network. Detection of an unauthorized server concludes as shown at step 312, with invalid server detector 207 calling invalid server denial handler 208.

5

INVALID SERVER DENIAL HANDLER

The invalid server denial handler component of the DHCP checker client is preferably a computer program. This component is responsible for: sending a large number of requests to each unauthorized DHCP server 204; and retrieving 212 configuration information from each unauthorized DHCP server 204 detected by the invalid server detector component. The requests include DHCPDISCOVER and DHCPREQUEST unicast messages, and utilizes the 'giaddr', 'chaddr', and 'ciaddr' fields of the messages. The number of the requests delivered from invalid server denial handler is a configuration parameter of the DHCP checker client.

10

09696513-103300

The invalid server denial handler, such as invalid server denial handler 208, simulates multiple DHCP clients to achieve the following goals. First, the client simulation prevents, to the extent possible, unauthorized DHCP servers 204 from responding to DHCP clients 201 that request configuration information. Client simulation further minimizes the number of DHCP clients 201 to which erroneous configuration information is provided by unauthorized DHCP servers 204 which in turn minimizes network access problems caused by the unauthorized DHCP servers.

25

30

These goals are achieved by sending a large number of requests **211** to each unauthorized DHCP server **204**, in order to overload each unauthorized DHCP server with the requests and the corresponding answers **212** and to reserve many if not all of the IP addresses allocatable by the unauthorized servers for the DHCP checker client. These reserved IP addresses are therefore no longer available for actual DHCP clients **201**.

As a consequence of client simulation operations performed by invalid server denial handler **208**, each the unauthorized DHCP server **204** is too busy to answer **214** requests sent **213** by actual DHCP clients **201**. The unauthorized servers are thus depleted of available IP addresses that can be provided to actual DHCP clients **201**. In this manner, the number of DHCP clients that retrieve **214** configuration information from the unauthorized DHCP servers is minimized.

Invalid server denial handler **208** is called by invalid server detector **207** when one or multiple unauthorized (invalid) DHCP servers have been detected. With reference now to **Figure 4**, there is illustrated a flow diagram depicting the logic flow of invalid server denial handler **208** in accordance with a preferred embodiment of the present invention.

The operation of invalid server denial handler **208** begins as depicted at step **401**, with invalid server denial handler **208** retrieving the identity of one DHCP server from "List_D". As previously explained with

reference to **Figure 3**, "List_D" includes the IP address of each unauthorized (invalid) DHCP server ("List_D" is built by the invalid server detector).

5 After retrieving the identity of the unauthorized server at step **401**, invalid server denial handler **208** determines if there is still at least one unauthorized DHCP server to process as shown at step **402**. If there is no DHCP server to process, all unauthorized DHCP servers detected by invalid server detector **207** have been
10 processed by invalid server denial handler **208** and as illustrated at step **403**, client simulation operations of invalid server denial handler **208** are paused. DHCP checker client **205** periodically initiates unauthorized server detection cycles performed by invalid server detector **207**. The inter-cycle period between such cycles is preferably a configuration parameter of DHCP checker client **205**.

09696548 "103500
30 If, as determined at step **402**, there remains at least one unauthorized DHCP server to process, then as illustrated at step **404**, invalid server denial handler **208** sends multiple DHCPREQUEST messages to the next unprocessed DHCP server. Invalid server denial handler
25 sends a large number of DHCPREQUEST messages to the specified DHCP server. The number of requests delivered is preferably a configuration parameter of DHCP checker client **205**. Each the DHCPREQUEST message sent at step
30 **404** has the following characteristics. Each message is a unicast message having as its destination the specified unauthorized DHCP server. Since the message is a unicast

message, the traffic within the IP network is minimized, and the impact of the traffic on the devices attached to the IP network is minimized (as compared to a broadcast message sent to all devices attached to the IP network). For example, the DHCP clients attached to the IP network do not have to waste time reading the unicast message (as opposed to a broadcast message, where each DHCP client has to read the broadcast message just to determine that it does not have to answer it).

A 'ciaddr' field included in each the DHCPREQUEST is set by invalid server denial handler 208 with an IP address that is not included within the range of the valid addresses utilized within the IP network. The range of valid IP addresses may be, for example, a configuration information of DHCP checker client 205, as provided by a network administrator. Since the DHCPREQUEST request received by the DHCP server includes an invalid (and therefore unknown) IP address in the 'ciaddr' field, a somewhat extended period of time will be required by the DHCP server before it determines that it cannot satisfy the request. During this time period, the DHCP server is busy and therefore is usually not able to respond to all the requests sent 213 by actual DHCP clients 201.

Proceeding to step 405, invalid server denial handler 208 sends multiple (preferably many) DHCPDISCOVER messages to the unauthorized DHCP server. The number of such discover messages sent by invalid server denial handler 208 is preferably a configuration parameter of DHCP checker client 205 (50 messages, for example). Each

DHCPDISCOVER message has the following characteristics. First, in a preferred embodiment of the present invention, each message is a unicast message having the unauthorized server as its destination. Since each message is an unicast message, the traffic impact of the messages within the IP network is minimized (as compared to a broadcast message that is sent to all devices attached to the IP network). For example, the DHCP clients attached to the IP network do not have to waste time reading the unicast message (as opposed to a broadcast message, where each DHCP client has to read the broadcast message just to determine that it does not have to answer it).

A 'chaddr' field included in each DHCPDISCOVER is set by invalid server denial handler 208 with a MAC address which is not included within a range of valid MAC addresses utilized within the IP network. The MAC address is therefore unknown within the IP network. The range of valid MAC addresses may be, for example, a configuration information of the DHCP checker client provided by a network administrator. This MAC address is selected such that it is not already utilized for another DHCPDISCOVER previously sent by the invalid server denial handler.

Since the DHCP server receives a DHCPDISCOVER request including a new unknown MAC address in the 'chaddr' field, the DHCP server reserves a new IP address for the MAC address. The IP address is reserved by the unauthorized server for DHCP checker client 205, and is therefore no longer available for other DHCP clients 201

The DHCP server reserves one IP address for the DHCP checker client, for each DHCPDISCOVER message. Since a large number of DHCPDISCOVER messages are received by the DHCP server, the DHCP server finally runs out of the available IP addresses that can be provided to DHCP clients **201**.

Optionally, the DHCPDISCOVER request also includes an "IP address lease time" option that is set to request a very long lease time (one week, for example) or even an infinite lease time. In such a case, the DHCP server reserves the IP address of DHCP checker client **205** for a very long associated with the MAC address included in the 'chaddr' field of the DHCPDISCOVER request. During the period in which the IP address is reserved, the DHCP server is not able to provide the IP address to the actual DHCP clients **201**.

Next, as depicted at step **406**, invalid server denial handler **208** waits for a message from the DHCP server. The message may be, for example, a DHCPOFFER message in response to a DHCPDISCOVER request. The period of time

over which invalid server denial handler **208** waits before receiving the messages is preferably a configuration parameter of DHCP checker client **205**.

Invalid server denial handler **208** then determines whether or not there is a DHCPOFFER message available for processing as shown at step **407**. The DHCPOFFER message includes the configuration information proposed by the DHCP server (including the proposed IP address). If there is no DHCPOFFER message to process, the denial of the specified DHCP server is complete. Other unauthorized DHCP servers may have to be denied. The invalid server denial handler loops to step **401** to retrieve the next unauthorized DHCP server to process.

If, as determined at step **407** there is a DHCPOFFER message to process in response to the DHCPDISCOVER message sent to the DHCP server, and as illustrated at step **408**, invalid server denial handler **208** sends a DHCPREQUEST message to the DHCP server. This DHCPREQUEST message is unicast to the specified DHCP server in order to accept the IP address proposed in the DHCPOFFER. The DHCPREQUEST is constructed in accordance with the DHCP protocol, using the information retrieved from the DHCPOFFER message. When the DHCP server receives the DHCPREQUEST message, it definitively reserves the proposed IP address, and this IP address cannot be allocated to another DHCP client. Invalid server denial handler then loops back to step **406** and waits for another message.

It should be noted that the step of flooding each unauthorized DHCP server with multiple IP address renewal requests and the step of reserving as many IP addresses as possible in each unauthorized DHCP server can be implemented together in a single embodiment as described above or independently in distinct embodiments.

ADVANTAGES

The present inventions provides the following advantages.

Unauthorized DHCP servers are detected, and can for example be physically removed from the IP network by a network administrator.

The negative effects generated by unauthorized DHCP servers within the IP network are limited. In particular, the number of DHCP clients receiving configuration information from the unauthorized DHCP servers is minimized. When the configuration information is in error, the number of DHCP clients in error is therefore minimized.

The traffic required within the IP network for detecting and neutralizing unauthorized DHCP servers is minimized. In particular, no broadcast message is utilized (only unicast messages are utilized) for the denial of unauthorized DHCP servers. Because each device within the IP network has to read broadcast messages, the broadcast messages have usually a negative impact on the performance of the devices. For example, a DHCP client has to read each broadcast message, just to determine

5

10

15

20

25

CLAIMS

What is claimed is:

1. A method for preventing unauthorized dynamic host configuration servers from responding to client configuration requests in an Internet Protocol (IP) network, said method comprising the steps of:

simulating a plurality of network clients within a server checker client;

detecting at least one unauthorized dynamic host configuration server within said IP network; and

delivering configuration requests from said server checker client to said at least one unauthorized dynamic configuration server such that said at least one unauthorized dynamic host configuration server is unable to respond to configuration requests from actual network clients.

2. The method of claim 1, further comprising the step of reserving multiple IP addresses in each of said at least one unauthorized dynamic host configuration server.

3. The method of claim 2, wherein said step of reserving multiple IP addresses in each of said at least one unauthorized dynamic host configuration server further comprises the step of delivering a plurality of different IP address requests to each of said at least one unauthorized dynamic host configuration server.

1 4. The method of claim 3, further comprising the step
2 of flooding each of said at least one unauthorized
3 dynamic host configuration server with a plurality of IP
4 address renewal requests.

1 5. The method of claim 4, wherein the step of flooding
2 each of said at least one unauthorized dynamic host
3 configuration server with a plurality of IP address
4 renewal requests comprises the steps of:

5 simulating a plurality of clients requesting renewal
6 of their IP address; and

7 delivering a plurality of different IP address
8 renewal requests from said simulated plurality of clients
9 to each of said at least one unauthorized dynamic host
10 configuration server.

1 6. The method of claim 5, wherein each IP address
2 request includes:

3 an unknown client medium access control (MAC)
4 address; and

5 an IP address of said server checker client.

1 7. The method of claim 4, wherein each IP address
2 renewal request includes an unknown client IP address.

1 8. The method of claim 1, wherein said step of
2 detecting an unauthorized dynamic host configuration
3 server further comprises the steps of:

4 delivering an IP address request from said simulated
5 network clients by:

6 broadcasting a request for an IP address to dynamic
7 host configuration servers over said IP network;

8 receiving one or more responses from one or more of
9 said dynamic host configuration servers;

10 identifying a specific dynamic host configuration
11 server that originated each of said responses; and

12 determining for each identified dynamic host
13 configuration server whether or not said identified
14 dynamic host configuration server is authorized referring
15 to a table, wherein said table includes a list of
16 authorized dynamic host configuration servers.

1 9. The method of claim 8, wherein said step of
2 identifying a specific dynamic host configuration server
3 that originated a response further comprises the step of
4 retrieving from each response an IP address of the
5 dynamic host configuration server that originated the
6 response.

1 10. The method of claim 8, wherein said table includes
2 an IP address for each authorized dynamic host
3 configuration server.

1 11. The method of claim 8, wherein each response
2 comprises a proposed IP address, and wherein said step of
3 determining for each identified dynamic host

4 configuration server whether or not said identified
5 dynamic host configuration server is authorized referring
6 to a table, further comprises the step of releasing a
7 proposed IP address to each identified dynamic host
8 configuration server.

1 12. The method of claim 11, wherein said releasing step
2 further comprises the step of broadcasting a release
3 message containing an IP address of an unknown dynamic
4 host configuration server to each of said identified
5 dynamic host configuration servers.

13. The method of claim 1, wherein said detecting step
is executed at predefined time intervals.

0916518-101500

1 14. A system for preventing unauthorized dynamic host
2 configuration servers from responding to client
3 configuration requests in an Internet Protocol (IP)
4 network, said system comprising:

5 processing means for simulating a plurality of
6 network clients within a server checker client;

7 processing means for detecting at least one
8 unauthorized dynamic host configuration server within
9 said IP network; and

10 processing means for delivering configuration
11 requests from said server checker client to said at least
12 one unauthorized dynamic configuration server such that
13 said at least one unauthorized dynamic host configuration
14 server is unable to respond to configuration requests
15 from actual network clients.

16 15. The system of claim 14, further comprising
17 processing means for reserving multiple IP addresses in
18 each of said at least one unauthorized dynamic host
19 configuration server.

20 16. The system of claim 15, wherein said processing
21 means for reserving multiple IP addresses in each of said
22 at least one unauthorized dynamic host configuration
23 server further comprises processing means for delivering
24 a plurality of different IP address requests to each of
25 said at least one unauthorized dynamic host configuration
26 server.
27

1 17. The system of claim 16, further comprising
2 processing means for flooding each of said at least one
3 unauthorized dynamic host configuration server with a
4 plurality of IP address renewal requests.

1 18. The system of claim 17, wherein said processing
2 means for flooding each of said at least one unauthorized
3 dynamic host configuration server with a plurality of IP
4 address renewal requests comprises:

5 processing means for simulating a plurality of
6 clients requesting renewal of their IP address; and

7 processing means for delivering a plurality of
8 different IP address renewal requests from said simulated
9 plurality of clients to each of said at least one
10 unauthorized dynamic host configuration server.

1 19. The system of claim 18, wherein each IP address
2 request includes:

3 an unknown client medium access control (MAC)
4 address; and

5 an IP address of said server checker client.

1 20. The system of claim 17, wherein each IP address
2 renewal request includes an unknown client IP address.

1 21. The system of claim 14, wherein said processing
2 means for detecting an unauthorized dynamic host
3 configuration server further comprises:

4 processing means for delivering an IP address
5 request from said simulated network clients by:

6 processing means for broadcasting a request for an
7 IP address to dynamic host configuration servers over
8 said IP network;

9 processing means for receiving one or more responses
10 from one or more of said dynamic host configuration
11 servers;

12 processing means for identifying a specific dynamic
13 host configuration server that originated each of said
14 responses; and

15 processing means for determining for each identified
16 dynamic host configuration server whether or not said
17 identified dynamic host configuration server is
18 authorized referring to a table, wherein said table
19 includes a list of authorized dynamic host configuration
20 servers.

1 22. The system of claim 21, wherein said processing
2 means for identifying a specific dynamic host
3 configuration server that originated a response further
4 comprises processing means for retrieving from each
5 response an IP address of the dynamic host configuration
6 server that originated the response.

1 23. The system of claim 21, wherein said table includes
2 an IP address for each authorized dynamic host
3 configuration server.

1 24. The system of claim 21, wherein each response
2 comprises a proposed IP address, and wherein said
3 processing means for determining for each identified
4 dynamic host configuration server whether or not said
5 identified dynamic host configuration server is
6 authorized referring to a table, further comprises
7 processing means for releasing a proposed IP address to
8 each identified dynamic host configuration server.

1 25. The system of claim 24, wherein said processing
2 means for releasing a proposed IP address to each
3 identified dynamic host configuration server further
4 comprises processing means for broadcasting a release
5 message containing an IP address of an unknown dynamic
6 host configuration server to each of said identified
7 dynamic host configuration servers.

1 26. The system of claim 14, wherein said processing
2 means for detecting at least one unauthorized dynamic
3 host configuration server is activated at predefined time
4 intervals.

1 27. A program product for preventing unauthorized
2 dynamic host configuration servers from responding to
3 client configuration requests in an Internet Protocol
4 (IP) network, said program product comprising:

5 instruction means for simulating a plurality of
6 network clients within a server checker client;

7 instruction means for detecting at least one
8 unauthorized dynamic host configuration server within
9 said IP network; and

10 instruction means for delivering configuration
11 requests from said server checker client to said at least
12 one unauthorized dynamic configuration server such that
13 said at least one unauthorized dynamic host configuration
14 server is unable to respond to configuration requests
15 from actual network clients.

16 28. The program product of claim 27, further comprising
17 instruction means for reserving multiple IP addresses in
18 each of said at least one unauthorized dynamic host
19 configuration server.

20 29. The program product of claim 28, wherein said
21 instruction means for reserving multiple IP addresses in
22 each of said at least one unauthorized dynamic host
23 configuration server further comprises instruction means
24 for delivering a plurality of different IP address
25 requests to each of said at least one unauthorized
26 dynamic host configuration server.
27

1 30. The program product of claim 29, further comprising
2 instruction means for flooding each of said at least one
3 unauthorized dynamic host configuration server with a
4 plurality of IP address renewal requests.

1 31. The program product of claim 30, wherein said
2 instruction means for flooding each of said at least one
3 unauthorized dynamic host configuration server with a
4 plurality of IP address renewal requests comprises:

5 instruction means for simulating a plurality of
6 clients requesting renewal of their IP address; and

7 instruction means for delivering a plurality of
8 different IP address renewal requests from said simulated
9 plurality of clients to each of said at least one
10 unauthorized dynamic host configuration server.

1 32. The program product of claim 31, wherein each IP
2 address request includes:

3 an unknown client medium access control (MAC)
4 address; and

5 an IP address of said server checker client.

1 33. The program product of claim 30, wherein each IP
2 address renewal request includes an unknown client IP
3 address.

1 34. The program product of claim 27, wherein said
2 instruction means for detecting an unauthorized dynamic

host configuration server further comprises:

instruction means for delivering an IP address request from said simulated network clients by:

instruction means for broadcasting a request for an IP address to dynamic host configuration servers over said IP network;

instruction means for receiving one or more responses from one or more of said dynamic host configuration servers;

instruction means for identifying a specific dynamic host configuration server that originated each of said responses; and

instruction means for determining for each identified dynamic host configuration server whether or not said identified dynamic host configuration server is authorized referring to a table, wherein said table includes a list of authorized dynamic host configuration servers.

35. The program product of claim 34, wherein said instruction means for identifying a specific dynamic host configuration server that originated a response further comprises instruction means for retrieving from each response an IP address of the dynamic host configuration server that originated the response.

1 36. The program product of claim 34, wherein said table
2 includes an IP address for each authorized dynamic host
3 configuration server.

1 37. The program product of claim 34, wherein each
2 response comprises a proposed IP address, and wherein
3 said instruction means for determining for each
4 identified dynamic host configuration server whether or
5 not said identified dynamic host configuration server is
6 authorized referring to a table, further comprises
7 instruction means for releasing a proposed IP address to
8 each identified dynamic host configuration server.

1 38. The program product of claim 37, wherein said
2 instruction means for releasing a proposed IP address to
3 each identified dynamic host configuration server further
4 comprises instruction means for broadcasting a release
5 message containing an IP address of an unknown dynamic
6 host configuration server to each of said identified
7 dynamic host configuration servers.


1 39. The program product of claim 27, wherein said
2 instruction means for detecting at least one unauthorized
3 dynamic host configuration server is activated at
4 predefined time intervals.

ABSTRACT OF THE DISCLOSURE


METHOD AND SYSTEM FOR PREVENTING UNAUTHORIZED SERVER
INTERFERENCE IN AN INTERNET PROTOCOL NETWORK


20


[illegible]



(Prior Art)







**DECLARATION AND POWER OF ATTORNEY
FOR PATENT APPLICATION**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; I believe I am an original, first and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**Method and System for Preventing Unauthorized Server Interference
in an Internet Protocol Network**

the specification of which is identified by the attorney (IBM) Docket Number appearing above.

I hereby state that I have reviewed and understand the contents of the above- identified specification, including the claims.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

| <u>Number</u> | <u>Country</u> | <u>Day/Month/Year</u> | <u>Priority Claimed</u> |
|---------------|----------------|-----------------------|-------------------------|
| 99480119.9 | Europe | 25/11/99 | Yes |

I hereby claim the benefit (a) under Title 35, United States Code, §119(e) of any U.S. application listed below and identified as a provisional application or (b) under Title 35, United States Code, §120 of any U.S. application listed below and not identified as a provisional application, and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior U.S. application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information material to the patentability of this application as defined in Title 37, Code of Federal Regulations, §1.56 which occurred between the filing date of the prior application and the national or PCT international filing date of this application

Prior U.S. Applications

| <u>Serial No.</u> | <u>Filing Date</u> | <u>Status</u> |
|-------------------|--------------------|---------------|
|-------------------|--------------------|---------------|

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

As a named inventor, I hereby appoint the following attorneys and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith: Daniel E. McConnell, Reg. No. 20,360; Joscelyn G. Cockburn, Reg. No. 27,069; Horace St. Julian, Reg. No. 30,329; and Christopher A. Hughes, Reg. No. 26,914.

Send all correspondence to: Daniel E. McConnell, IBM Corporation 2Y7/B656; PO Box 12195; Research Triangle Park, NC 27709.

First Inventor:

Olivier Daude

Signature:

Olivier Daude



Oct 13, 2000

Date

Residence: Residence La Vigie
169, avenue de Fabron
06200 Nice - France

Citizenship: French

Post Office Address: Same as above

Second Inventor:

Olivier Hericourt

Signature:

Olivier Hericourt

Oct 9, 2000

Date

Residence: Residence Le Flore
62, chemin du Val Fleuri
06800 Cagnes Sur Mer- France

Citizenship: French

Post Office Address: Same as above